

型 号 Model	MU4H7. 62		
间 距 Pitch	7. 62mm		
认 证 Approval			
UL 数 据 UL Technical Data	B	C	D
电 压 Nom. Voltage (V)	300		
电 流 Nom. Current (A)	30		
连接线径 Wire Size (AWG)	28-10		
IEC 数据 IEC Toohnical Data			
材料组别 Material Group	I		
过电类型 Surge Voltage Category	III	III	II
污染等级 Contamination Calass	3	2	2
额定电压 Rated Voltage (V)	500	630	1000
冲击电压 Rated Surge Voltage (KV)	6	6	6
电流/导线 Current (A)/Cross Section	32/4		
连接容量 Connection Capacity			
单股导线 Solid (mm ²)	0. 2-6		
多股导线 Strand (mm ²)	0. 2-4		
美规导线 Wire Sizes (AWG)	28-10		
额定扭力 Torque (N* m)	0. 5-0. 6		
剥线长度 Stripping Length (mm ²)	8		
材 料 Material			
绝缘材料 Insulation Material	PA		
阻燃等级 Inflammability Class (UL94)	V0		
导电压片 Contact	黄铜/Brass		
螺 钉 Screw	M3 钢/M3 Steel		
使用温度 Operation Temperature (℃)	-40℃ ~+105℃		
位 数 No. of Position	型号 Model		
	2	MU4H7. 62/2-GN	
	3	MU4H7. 62/3-GN	
产品状态 Product Status			
外形图 Dimension			