

型 号 Model		MU2. 5H2/5. 08		
间 距 Pitch		5. 08mm		
认 证 Approval		UL CE		
UL 数 据 UL Technical Data		B	C	D
电 压 Nom. Voltage (V)		300		
电 流 Nom. Current (A)		20		
连接线径 Wire Size (AWG)		30-12		
IEC 数据 IEC Toohnical Data				
材料组别 Material Group		I		
过电类型 Surge Voltage Category		III	III	III
污染等级 Contamination Calass		3	2	2
额定电压 Rated Voltage (V)		250	400	630
冲击电压 Rated Surge Voltage (KV)		4	4	4
电流/导线 Current (A)/Cross Section		24/2. 5		
连接容量 Connection Capacity				
单股导线 Solid (mm²)		0. 2-4		
多股导线 Strand (mm²)		0. 2-2. 5		
美规导线 Wire Sizes (AWG)		30-12		
额定扭力 Torque (N* m)		0. 5-0. 6		
剥线长度 Stripping Length (mm²)		8		
材 料 Material				
绝缘材料 Insulation Material		PA		
阻燃等级 Inflammability Class (UL94)		V0		
导电压片 Contact		黄铜/Brass		
螺 钉 Screw		M3 钢/M3 Steel		
使用温度 Operation Temperature (°C)		-40°C ~+105°C		
位 数 No. of Position		型号 Model		
		2	MU2. 5H2/5. 08/2-GN	
		3	MU2. 5H2/5. 08/3-GN	
产品状态 Product Status				
外形图 Dimension				
				