

型 号 Model	MU2. 5CA/H5. 00		
间 距 Pitch	5. 00mm		
认 证 Approval	UL CE		
UL 数 据 UL Technical Data	B	C	D
电 压 Nom. Voltage (V)	300		
电 流 Nom. Current (A)	20		
连接线径 Wire Size (AWG)	30-12		
IEC 数据 IEC Toohnical Data			
材料组别 Material Group	I		
过电类型 Surge Voltage Category	III	III	III
污染等级 Contamination Calass	3	2	2
额定电压 Rated Voltage (V)	250	320	630
冲击电压 Rated Surge Voltage (KV)	4	4	4
电流/导线 Current (A)/Cross Section	24/2. 5		
连接容量 Connection Capacity			
单股导线 Solid (mm²)	0. 2-4. 0		
多股导线 Strand (mm²)	0. 2-2. 5		
美规导线 Wire Sizes (AWG)	30-12		
额定扭力 Torque (N* m)	0. 5-0. 6		
剥线长度 Stripping Length (mm²)	9		
材 料 Material			
绝缘材料 Insulation Material	PA		
阻燃等级 Inflammability Class (UL94)	V0		
导电压片 Contact	黄铜/Brass		
螺 钉 Screw	M2. 5 钢/M2. 5 Steel		
使用温度 Operation Temperature (℃)	-40℃ ~+105℃		
位 数 No. of Position	型号 Model		
	2	MU2. 5CA/H5. 00/2-GN	
	3	MU2. 5CA/H5. 00/3-GN	
		...	
	24	MU2. 5CA/H5. 00/24-GN	
产品状态 Product Status	MU2. 5CA/H5. 00 开发中		
外形图 Dimension			