

型 号 Model		MU1. 5P/H5. 0 (5. 08)		
间 距 Pitch		5. 00 (5. 08) mm		
认 证 Approval		UL CE		
UL 数 据 UL Technical Data		B	C	D
电 压 Nom. Voltage (V)		300		
电 流 Nom. Current (A)		15		
连接线径 Wire Size (AWG)		26-14		
IEC 数据 IEC Toohnical Data				
材料组别 Material Group		I		
过电类型 Surge Voltage Category		III	III	II
污染等级 Contamination Calass		3	2	2
额定电压 Rated Voltage (V)		250	320	630
冲击电压 Rated Surge Voltage (KV)		4	4	4
电流/导线 Current (A)/Cross Section		17. 5/1. 5		
连接容量 Connection Capacity				
单股导线 Solid (mm ²)		0. 2-2. 5		
多股导线 Strand (mm ²)		0. 2-1. 5		
美规导线 Wire Sizes (AWG)		26-14		
额定扭力 Torque (N* m)		0. 6		
剥线长度 Stripping Length (mm ²)		5		
材 料 Material				
绝缘材料 Insulation Material		PA		
阻燃等级 Inflammability Class (UL94)		V0		
导电压片 Contact		黄铜/Brass		
螺 钉 Screw		M2. 5 钢/M2. 5 Steel		
使用温度 Operation Temperature (°C)		-40℃ ~ +105℃		
位 数 No. of Position		型号 Model		
		2	MU1. 5P/H5. 0 (5. 08) /2-GN	
		3	MU1. 5P/H5. 0 (5. 08) /3-GN	
产品状态 Product Status		MU1. 5P/H5. 08 开发中		
外形图 Dimension				



