

型 号 Model	MU1. 5SP/HD3. 81		
间 距 Pitch	3. 81mm		
认 证 Approval	CE		
UL 数 据 UL Technical Data	B	C	D
电 压 Nom. Voltage (V)	300		300
电 流 Nom. Current (A)	10		10
连接线径 Wire Size (AWG)	20-16		20-16
IEC 数据 IEC Toohnical Data			
材料组别 Material Group	I		
过电类型 Surge Voltage Category	III	III	II
污染等级 Contamination Calass	3	2	2
额定电压 Rated Voltage (V)	160	160	320
冲击电压 Rated Surge Voltage (KV)	2.5	2.5	2.5
电流/导线 Current(A)/Cross Section	17. 5/1. 5		
连接容量 Connection Capacity			
单股导线 Solid (mm ²)	0. 5-1. 5		
多股导线 Strand (mm ²)	0. 5-1. 5		
美规导线 Wire Sizes (AWG)	20-16		
额定扭力 Torque (N* m)	-		
剥线长度 Stripping Length (mm ²)	10		
材 料 Material			
绝缘材料 Insulation Material	PA		
阻燃等级 Inflammability Class (UL94)	V0		
导电压片 Contact	黄铜/Brass		
螺 钉 Screw	-		
使用温度 Operation Temperature (℃)	-40℃ ~+105℃		
位 数 No. of Position	型号 Model		
	2	MU1. 5SP/HD3. 81/2-GN	
	3	MU1. 5SP/HD3. 81/3-GN	
	...	...	
	24	MU1. 5SP/HD3. 81/24-GN	
产品状态 Product Status			

外形图 Dimension	
	