

|                                          |  |                                                                                        |                       |          |
|------------------------------------------|--|----------------------------------------------------------------------------------------|-----------------------|----------|
| 型 号 Model                                |  | MU1. 5SP/AD3. 5                                                                        |                       |          |
| 间 距 Pitch                                |  | 3. 50mm                                                                                |                       |          |
| 认 证 Approval                             |  | CE  |                       |          |
| UL 数 据 UL Technical Data                 |  | B                                                                                      | C                     | D        |
| 电 压 Nom. Voltage (V)                     |  | 300                                                                                    |                       | 300      |
| 电 流 Nom. Current (A)                     |  | 5                                                                                      |                       | 10       |
| 连接线径 Wire Size (AWG)                     |  | 20-16sol                                                                               |                       | 20-16sol |
| IEC 数据 IEC Toohnical Data                |  |                                                                                        |                       |          |
| 材料组别 Material Group                      |  | I                                                                                      |                       |          |
| 过电类型 Surge Voltage Category              |  | III                                                                                    | III                   | II       |
| 污染等级 Contamination Calass                |  | 3                                                                                      | 2                     | 2        |
| 额定电压 Rated Voltage (V)                   |  | 160                                                                                    |                       | 320      |
| 冲击电压 Rated Surge Voltage (KV)            |  | 2.5                                                                                    |                       | 2.5      |
| 电流/导线 Current(A)/Cross Section           |  | 5/0. 75                                                                                |                       |          |
| 连接容量 Connection Capacity                 |  |                                                                                        |                       |          |
| 单股导线 Solid (mm <sup>2</sup> )            |  | 0. 5-0. 75                                                                             |                       |          |
| 多股导线 Strand (mm <sup>2</sup> )           |  | -                                                                                      |                       |          |
| 美规导线 Wire Sizes (AWG)                    |  | 22-18                                                                                  |                       |          |
| 额定扭力 Torque (N* m)                       |  | -                                                                                      |                       |          |
| 剥线长度 Stripping Length (mm <sup>2</sup> ) |  | 8                                                                                      |                       |          |
| 材 料 Material                             |  |                                                                                        |                       |          |
| 绝缘材料 Insulation Material                 |  | PA                                                                                     |                       |          |
| 阻燃等级 Inflammability Class (UL94)         |  | V0                                                                                     |                       |          |
| 导电压片 Contact                             |  | 黄铜/Brass                                                                               |                       |          |
| 螺 钉 Screw                                |  | -                                                                                      |                       |          |
| 使用温度 Operation Temperature (℃)           |  | -40℃ ~+105℃                                                                            |                       |          |
| 位 数 No. of Position                      |  | 型号 Model                                                                               |                       |          |
|                                          |  | 2                                                                                      | MU1. 5SP/AD3. 5/2-GN  |          |
|                                          |  | 3                                                                                      | MU1. 5SP/AD3. 5/3-GN  |          |
|                                          |  | ...                                                                                    | ...                   |          |
|                                          |  | 24                                                                                     | MU1. 5SP/AD3. 5/24-GN |          |
| 产品状态 Product Status                      |  |                                                                                        |                       |          |
| 外形图 Dimension                            |  |                                                                                        |                       |          |



