

型 号 Model		MU2. 5SP/HD5. 08		
间 距 Pitch		5. 08mm		
认 证 Approval		CE		
UL 数 据 UL Technical Data		B	C	D
电 压 Nom. Voltage	(V)	300		300
电 流 Nom. Current	(A)	10		10
连接线径 Wire Size	(AWG)	20-14		20-14
IEC 数据 IEC Toohnical Data				
材料组别 Material Group		I		
过电类型 Surge Voltage Category		III	III	II
污染等级 Contamination Calass		3	2	2
额定电压 Rated Voltage	(V)	320	320	630
冲击电压 Rated Surge Voltage	(KV)	2.5	2.5	2.5
电流/导线 Current (A)/Cross Section		24/2. 5		
连接容量 Connection Capacity				
单股导线 Solid	(mm ²)	0. 5-2. 5		
多股导线 Strand	(mm ²)	0. 5-2. 5		
美规导线 Wire Sizes	(AWG)	14-20		
额定扭力 Torque	(N* m)	-		
剥线长度 Stripping Length	(mm ²)	10		
材 料 Material				
绝缘材料 Insulation Material		PA		
阻燃等级 Inflammability Class	(UL94)	V0		
导电压片 Contact		黄铜/Brass		
螺 钉 Screw		-		
使用温度 Operation Temperature	(℃)	-40℃ ~+105℃		
位 数 No. of Position		型号 Model		
		2	MU2. 5SP/HD5. 08/2-GN	
		3	MU2. 5SP/HD5. 08/3-GN	
		...	...	
		24	MU2. 5SP/HD5. 08/24-GN	
产品状态 Product Status		MU2. 5SP/HD5. 08 开发中		
外形图 Dimension				
				