

型 号 Model		MA1. 5/VR3. 50(3. 81)		
间 距 Pitch		3. 50(3. 81)mm		
认 证 Approval		UL CE		
UL 数 据 UL Technical Data		B	C	D
电 压 Nom. Voltage (V)		300		
电 流 Nom. Current (A)		8		
连接线径 Wire Size (AWG)		30-16		
IEC 数据 IEC Toohnical Data				
材料组别 Material Group		I		
过电类型 Surge Voltage Category		III	III	II
污染等级 Contamination Calass		3	2	2
额定电压 Rated Voltage (V)		160	160	320
冲击电压 Rated Surge Voltage (KV)		2.5	2.5	2.5
电流/导线 Current (A)/Cross Section		8/1. 5		
连接容量 Connection Capacity				
单股导线 Solid (mm ²)		0. 08-1. 5		
多股导线 Strand (mm ²)		0. 08-1. 5		
美规导线 Wire Sizes (AWG)		30-16		
额定扭力 Torque (N* m)		0. 22-0. 25		
剥线长度 Stripping Length (mm ²)		7		
材 料 Material				
绝缘材料 Insulation Material		PA		
阻燃等级 Inflammability Class (UL94)		V0		
导电压片 Contact		黄铜/Brass		
螺 钉 Screw		M2 钢/M2 Steel		
使用温度 Operation Temperature (℃)		-40℃ ~+105℃		
位 数 No. of Position		型号 Model		
		2	MA1. 5/VR3. 50(3. 81)/2-GN	
		3	MA1. 5/VR3. 50(3. 81)/3-GN	
		24	MA1. 5/VR3. 50(3. 81)/24-GN	
产品状态 Product Status				
外形图 Dimension				
				