


型 号 Model	MA2. 5/H5. 0 (5. 08)		
间 距 Pitch	5. 0 (5. 08) mm		
认 证 Approval			
UL 数 据 UL Technical Data	B	C	D
电 压 Nom. Voltage (V)	300	300	
电 流 Nom. Current (A)	18	10	
连接线径 Wire Size (AWG)	30-12	30-12	
IEC 数据 IEC Toohnical Data			
材料组别 Material Group	I		
过电类型 Surge Voltage Category	III	III	II
污染等级 Contamination Calass	3	2	2
额定电压 Rated Voltage (V)	250	320	630
冲击电压 Rated Surge Voltage (KV)	4	4	4
电流/导线 Current(A)/Cross Section	18/2. 5		
连接容量 Connection Capacity			
单股导线 Solid (mm ²)	0. 14-2. 5		
多股导线 Strand (mm ²)	0. 14-2. 5		
美规导线 Wire Sizes (AWG)	30-12		
额定扭力 Torque (N* m)	0. 60		
剥线长度 Stripping Length (mm ²)	7		
材 料 Material			
绝缘材料 Insulation Material	PA		
阻燃等级 Inflammability Class (UL94)	V0		
导电压片 Contact	磷铜		
螺 钉 Screw	M3 钢/M3 Steel		
使用温度 Operation Temperature (℃)	-40℃ ~+105℃		
位 数 No. of Position	型号 Model		
	2	MA2. 5/H5. 0 (5. 08) /2-GN	
	3	MA2. 5/H5. 0 (5. 08) /3-GN	
	24	MA2. 5/H5. 0 (5. 08) /24-GN	
产品状态 Product Status			

外形图 Dimension	 
---------------	--