

型 号 Model		MB2. 5/V7. 62		
间 距 Pitch		7. 62mm		
认 证 Approval		UL CE		
UL 数 据 UL Technical Data		B	C	D
电 压 Nom. Voltage (V)		300		300
电 流 Nom. Current (A)		18		10
连接线径 Wire Size (AWG)		-		-
IEC 数据 IEC Toohnical Data				
材料组别 Material Group		I		
过电类型 Surge Voltage Category		III	III	II
污染等级 Contamination Calass		3	2	2
额定电压 Rated Voltage (V)		400	630	1000
冲击电压 Rated Surge Voltage (KV)		6	6	6
电流/导线 Current(A)/Cross Section		18/-		
材 料 Material				
绝缘材料 Insulation Material		PA		
阻燃等级 Inflammability Class (UL94)		V0		
端子材料 Terminal Material		黄铜/Brass		
端子镀层 Terminal Platting		锡 Tin-plated		
PCB 孔径 PCB Hole Diameter		Φ 1. 6mm		
使用温度 Operation Temperature (℃)		-40℃~+105℃		
位 数 No. of Position		型号 Model		
2		MB2. 5/V7. 62/2-GN		
3		MB2. 5/V7. 62/3-GN		
...		...		
12		MB2. 5/V7. 62/12-GN		
产品状态 Product Status				
外 形 图 Dimension				
				