

型 号 Model	MB2. 5/HF7. 62		
间 距 Pitch	7. 62mm		
认 证 Approval			
UL 数 据 UL Technical Data	B	C	D
电 压 Nom. Voltage (V)	300		300
电 流 Nom. Current (A)	18		10
连接线径 Wire Size (AWG)	-		-
IEC 数据 IEC Toohnical Data			
材料组别 Material Group	I		
过电类型 Surge Voltage Category	III	III	II
污染等级 Contamination Calass	3	2	2
额定电压 Rated Voltage (V)	400	630	1000
冲击电压 Rated Surge Voltage (KV)	6	6	6
电流/导线 Current(A)/Cross Section	18/-		
材 料 Material			
绝缘材料 Insulation Material	PA		
阻燃等级 Inflammability Class (UL94)	V0		
端子材料 Terminal Material	黄铜/Brass		
端子镀层 Terminal Platting	锡 Tin-plated		
PCB 孔径 PCB Hole Diameter	Φ1. 6mm		
使用温度 Operation Temperature (℃)	-40℃~+105℃		
位 数 No. of Position	型号 Model		
2	MB2. 5/HF7. 62/2-GN		
3	MB2. 5/HF7. 62/3-GN		
...	...		
12	MB2. 5/HF7. 62/12-GN		
产品状态 Product Status			
外形图 Dimension			