

型 号 Model		MB1. 5H/H3. 81		
间 距 Pitch		3.81mm		
认 证 Approval		UL CE		
UL 数 据 UL Technical Data		B	C	D
电 压 Nom. Voltage	(V)	300		
电 流 Nom. Current	(A)	8		
连接线径 Wire Size	(AWG)	-		
IEC 数据 IEC Toohnical Data				
材料组别 Material Group		I		
过电类型 Surge Voltage Category		III	III	II
污染等级 Contamination Calass		3	2	2
额定电压 Rated Voltage	(V)	160	160	320
冲击电压 Rated Surge Voltage	(KV)	2.5	2.5	2.5
电流/导线 Current(A)/Cross Section		8/-		
材 料 Material				
绝缘材料 Insulation Material		PA		
阻燃等级 Inflammability Class	(UL94)	V0		
端子材料 Terminal Material		黄铜/Brass		
端子镀层 Terminal Platting		锡 Tin-plated		
PCB 孔径 PCB Hole Diameter		Φ1.3mm		
使用温度 Operation Temperature	(℃)	-40℃~+105℃		
位 数 No. of Position		型号 Model		
2		MB1. 5H/H3. 81/2-GN		
3		MB1. 5H/H3. 81/3-GN		
...		...		
24		MB1. 5H/H3. 81/24-GN		
产品状态 Product Status				
外 形 图 Dimension				
				