
























说明	简图	型号
<p>端子: 带通用安装在 NS32 型, 或 NS35 型导轨上。</p> <p>Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35 </p>		<div>JUT1-50</div> <div>厚/宽 高/ 高20.2/71.3/77.2/82.4</div> <div>Thickness/width Height/ Height</div> <div>刚性导线(mm<sup>2</sup>) 柔性导线(mm<sup>2</sup>) I U</div> <div>Rigid cable Solf cable (A) (V)</div> <div>AWG:6-0 16-50 25-50 150 1000</div> <div>IEC 60947-7-1</div>
<p>1. 中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 桥前须将外壳的隔片打通.</p> <p>Central adaptor:used at the center of terminal to realize crosswise bridging,and thescrew head has insylation circle,the outer-case isolation slice should be get through before briging</p>	<div>2位 </div> <div>3位 </div>	<div>JFB2-50</div> <div>JFB3-50</div>
<p>2.边插式联络件: 全绝缘.插入压线框中,并上海在端子绝缘外壳上.</p> <p>Side adaptor:The whole-insulation is inserted into wire –pressing frame, additionally,it should be blocked onto terminal’s insulation outer-case.</p>	<div>2位 </div> <div>3位 </div>	-
<p>3.分接端子:用于连接大电流的较小截面的导线, 以实现额定工作电压至 1000V 大电流分接.</p> <p>Tapping terminal:used to connect great-current lead with smaller section to realize great-current tapping with rated work voltage being 1000v</p>		JUT1-50FJ-
<p>4.棱柱补偿块:垫平压线框棱形底面,以连接扁平导线.</p> <p>Prism compensation-lump:leveling up prism bottom side of wirepressing frame to be connected with flat lead.</p>		JUT1-50EP
<p>5.终端固定件:标记夹和标记条可卡在它上面进行标识.另对端子排终端起固定件作用(JUT1 系列通用)</p> <p>Terminal fixed component:mark clamp and marl strip could be blocked onto it to mark it, additionally,it could be used as fixed component to terminal row’s termination(universal for JUT1 serues)</p>		E/1
<p>6. 标记条: 有横向和竖向两种字体, 10 位。</p> <p>Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced</p>	<div></div> <div></div>	ZB10
<p>7. 标记端子:用来对端子排进行标示,可安装在 型,或 型导轨上,端子带插入式标记条,书写面积:44X17mm<sup>2</sup>(标记端子 JUT1 系列产品通用)</p> <p>Mark terminal:used to mark terminalrow,it canbe installed on the type and type track,the terminal owns inserted-type mark strip with writing area of 44X17mm<sup>2</sup> (universal for series product with JUT1 mark terminal)</p>		JUT1-B