



说明	简图	型号
端子：带通用安装在 NS32 型，或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT1-240 厚/宽 高/ 高 36.6/102/126.4/131.9 Thickness/width Height/ Height 刚性导线(mm²) 柔性导线(mm²) I U Rigid cable Solf cable (A) (V) AWG:00-500 70-240 70-240 415 1000 IEC 60947-7-1
1. 中心联络件：用于端子中央，实现横向桥接，螺钉头带绝缘圈，桥前须将外壳的隔片打通。 Central adaptor.used at the center of terminal to realize crosswise bridging,and the screw head has insylation circle,the outer-case isolation slice should be get through before briging		-
2.边插式联络件：全绝缘.插入压线框中,并上海在端子绝缘外壳上。 Side adaptor:The whole-insulation is inserted into wire -pressing frame, additionally,it should be blocked onto terminal's insulation outer-case.		JEB2-240 JEB3-240
3.分接端子:用于连接大电流的较小截面的导线,以实现额定工作电压至 1000V 大电流分接。 Tapping terminal:used to connect great-current lead with smaller section to realize great-current tapping with rated work voltage being 1000v		JUT1-240FJ-
4.棱柱补偿块:垫平压线框棱形底面,以连接扁平导线。 Prism compensation-lump:leveling up prism bottom side of wirepressing frame to be connected with flat lead.		JUT1-150/240EP
5.终端固定件:标记夹和标记条可卡在它上面进行标识.另对端子排终端起固定件作用(JUT1 系列通用) Terminal fixed component:mark clamp and marl strip could be blocked onto it to mark it, additionally,it could be used as fixed component to terminal row's termination(universal for JUT1 serues)		E/1
6. 标记条：有横向和竖向两种字体，10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced		ZB10
7. 标记端子:用来对端子排进行标示,可安装在 型,或 型导轨上,端子带插入式标记条,书写面积:44X17mm²(标记端子 JUT1 系列产品通用) Mark terminal:used to mark terminalrow,it canbe installed on the type and type track,the terminal owns inserted-type mark strip with writing area of 44X17mm² (universal for series product with JUT1 mark terminal)		JUT1-B