


说明	简图	型号
端子：带通用安装在 NS32 型，或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT1-35B 厚/宽 高/ 高 15.2/56/52/57 Thickness/width Height/ Height 刚性导线(mm²) 柔性导线(mm²) I U Rigid cable Solf cable (A) (V) AWG:18-0 0.75-35 0.75-35 25 800 IEC 60947-7-1
1.端板 End plate		封闭型外壳，不用端板。 Sealed outer-case,don't need end plate
2. 中心联络件：用于端子中央，实现横向桥接，螺钉头带绝缘圈，可分：2-位,3-位,5-位,10-位。 Central adaptor.used at the center of terminal for transverse bridge connection, and screw head with insulated ring,which is dived into:2-digit, 3-digit, 5-digit, 10-digit,		JFB2-35 JFB3-35
3.边插式联络件：全绝缘 2 位；全绝缘 3 位，全绝缘 10 位。 Side adaptor:Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit		JEB10-35
4.绝缘隔片：用于相邻联络格件的电气隔离；可事后插入；不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors;they may be inserted afterwards, and not occupy any space of track.		JS-K
5.分组隔片：用于端子组间的视角及电气隔离。 Segment spacer; for visual and electric separation between neigh boring terminal groups.		-
6.测试插座：与测试插头形成测试连接 Test socket; to form a testing connection by using test plug.		PSB6/5/6
7.测试插头：与测试插座形成测试连接 Test plug: to form a testing connection by using test socket.		PS
8.标记条：有横向和竖向两种字体，10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced.		ZB10
9.警示牌 Warning board		JW15