






说明	简图	型号
端子：带通用安装在 NS32 型，或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT1-2.5/2L 厚/宽 高/ 高 5.2/56/62/67 Thickness/width Height/ Height 刚性导线(mm²) 柔性导线(mm²) I U Rigid cable Solf cable (A) (V) AWG:24-12 0.2-4 0.2-2.5 32 500 IEC 60947-7-1
1.端板 End plate		G-JUT1-2.5/4
2. 中心联络件：用于端子中央，实现横向桥接，螺钉头带绝缘圈，可分：2-位,3-位,5-位,10-位。 Central adaptor.used at the center of terminal for transverse bridge connection, and screw head with insulated ring,which is dived into:2-digit, 3-digit, 5-digit, 10-digit,		JFBN10-2.5
3.边插式联络件：全绝缘 2 位；全绝缘 3 位，全绝缘 10 位。 Side adaptor:Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit		JEB2-2.5 JEB3-2.5 JEB10-2.5
4.跨接联络件：10 位，可分，带 10 枚螺钉；可形成跳过某些端子的跨接。 Cross connection adaptorin 10 digit,detachable,with 10 screws, for cross connection by overleaping some terminals		JB110-2.5
5.绝缘隔片：用于相邻联络格件的电气隔离；可事后插入；不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors;they may be inserted afterwards, and not occupy any space of track.		JS-KK3
6.补偿端板：与普通端子相邻排列时，用来抵消层间错位，厚 2.5mm。 Compensation header:when laid adjacently to common terminal,it can offset error betweenlayers,with thickness of 2.5mm		DG-JUT1-2.5/4
7. 补偿端板：与普通端子相邻排列时，用来抵消层间错位，厚 2.5mm。 Compensation header:when laid adjacently to common terminal,it can offset error betweenlayers,with thickness of 2.5mm		DP-JUT1-2.5/4
8.标记条：有横向和竖向两种字体，10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced.		ZB5
9.警示牌 Warning board		JWS5