












说明	简图	型号
<p>端子：可安装在 NS15 型导轨上。</p> <p>Terminal: can be installed on tracks</p> <p>NS15 type</p>		<p>JUT1-6E</p> <p>厚/宽 高 5.2/32/36</p> <p>Thickness/width Height</p> <p>刚性导线(mm²) 柔性导线(mm²) I U</p> <p>Rigid cable Solf cable (A) (V)</p> <p>AWG:24-10 0.5-10 0.5-6 57 500</p> <p>IEC 60947-7-1</p>
1.端板 End plate		G-JUT1-6E
2. 中心联络件：用于端子中央，实现横向桥接，螺钉头带绝缘圈，可分：2-位,3-位,5-位,10-位。 Central adaptor.used at the center of terminal for transverse bridge connection, and screw head with insulated ring,which is dived into:2-digit, 3-digit, 5-digit, 10-digit,		JFB10-6
3.边插式联络件：全绝缘 2 位；全绝缘 3 位，全绝缘 10 位。 Side adaptor:Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit		JEB2-6 JEB3-6 JEB10-6
4.跨接联络件：10 位，可分，带 10 枚螺钉；可形成跳过某些端子的跨接。 Cross connection adaptorin 10 digit,detachable,with 10 screws, for cross connection by overleaping some terminals		JB110-6-
5.绝缘隔片：用于相邻联络格件的电气隔离；可事后插入；不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors;they may be inserted afterwards, and not occupy any space of track.		JS-KK3
6.分组隔片：用于端子组间的视角及电气隔离。 Segment spacer; for visual and electric separation between neigh boring terminal groups.		-
7.测试插座：与测试插头形成测试连接 Test socket; to form a testing connection by using test plug.		JAP-E
8.标记条：有横向和竖向两种字体，10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced.		PSB4/7/6
9.终端固定件：标记夹和标记条可卡在它上面进行标识。另对端子排终端起固定件作用（JUT2 系列通用） Terminal fixed component:mark clamp and marl strip could be blocked onto it to mark it, additionally,it could be used as fixed component to teminal row's termination(universal for JUT2 serues)		ZB8
10.安装轨（NS15/5.5） Installment track(NS15/5.5)		E/1E
		NS15/5.5