






说明	简图	型号
端子: 带通用安装在 NS32 型, 或 NS35 型导轨上。 Terminal: with general-purpose mounting feet, can be installed on tracks NS32 or NS35		JUT2-4 厚/宽 高/ 高 6.5/42/47.5/52 Thickness/width Height/ Height 额定截面 Rated section: 4mm² I U (A) (V) AWG: 24-14 32 800 IEC 60947-7-1
1. 端板 End plate		G-JUT2-4/10
2. 分组隔板: 用于端子组间的视角及电气隔离。 Insulating spacer: for visual and electric separation between neighboring terminal groups.		TW4/10
3. 绝缘隔片: 用于相邻联络件的电气隔离; 可事后插入; 不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors; they may be inserted afterwards, and not occupy any space of track		TS2.5/35
4. 中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 可分: 2-位, 3-位, 5-位, 10-位。 Central adaptor. used at the center of terminal for transverse bridge connection, and screw head with insulated ring, which is divided into: 2-digit, 3-digit, 5-digit, 10-digit.		JQ2-4 JQ3-4 JQ10-4
5. 跨接联络件: 10 位, 可分, 带 10 枚螺钉; 可形成跳过某些端子的跨接。 Cross connection adaptor in 10 digit, detachable, with 10 screws, for cross connection by overleaping some terminals		JSQ10-4
6. 标记条: 有横向和竖向两种字体, 10 位。 Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.		DEK5
7. 终端固定件: 对端子排终端起固定作用 (JUT2 系列通用) Terminal fixed component: mark it could be used as fixed component to terminal row's termination (universal for JUT2 series)		E/2
8. 安装轨 (NS35/7.5) Installment track (NS35/7.5)		NS35/7.5
9. 终端固定件 Terminal fixed component		E/4
10. 安装轨 (NS35/7.5) Installment track (NS35/7.5)		NS32/15