






说明	简图	型号
端子:带通用安装在 NS32 型,或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT2-35 厚/宽 高/ 高 18/58/63.5/68 Thickness/width Height/ Height 额定截面 Rated section:35mm² I U (A) (V) AWG:18-0 125 800 IEC 60947-7-1
1.端板 End plate		G-JUT2-35
2.分组隔板:用于端子组间的视角及电气隔离。 Insulating spacer:for visual and electric separation between neighboring terminal groups.		TW35
3. 绝缘隔片:用于相邻联络件的电气隔离;可事后插入;不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors;they may be inserted afterwards, and not occupy any space of track		TS2.5/35
4. 中心联络件:用于端子中央,实现横向桥接,螺钉头带绝缘圈,可分: 2-位,3-位,5-位,10-位。 Central adaptor. used at the center of terminal for transverse bridge connection, and screw head with insulated ring,which is dived into:2-digit, 3-digit, 5-digit, 10-digit,		JQ2-35 JQ3-35
5. 跨接联络件: 10 位, 可分, 带 10 枚螺钉;可形成跳过某些端子的跨接。 Cross connection adaptorin 10 digit,detachable,with 10 screws, for cross connection by overleaping some terminals		JSQ3-35
6. 标记条: 有横向和竖向两种字体, 10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced.		DEK5
7. 终端固定件: 对端子排终端起固定作用 (JUT2 系列通用) Terminal fixed component:mark it could be used as fixed component to terminal row's termination (universal for JUT2 series)		E/2
8. 安装轨 (NS35/7.5) Installment track (NS35/7.5)		NS35/7.5
9.终端固定件 Terminal fixed component		E/4
10. 安装轨 (NS32/7.5) Installment track (NS32/7.5)		NS32/15