






说明	简图	型号
端子:带通用安装在 NS32 型,或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT2-4/2 厚 / 宽 / 高 6/54/60 Thickness/width/Height 额定截面 Rated section:4mm² I U (A) (V) AWG:24-10 32 500 IEC 60947-7-1
1.端板 End plate		G-JUT2-4/2
2.分组隔板:用于端子组间的视角及电气隔离。 Insulating spacer:for visual and electric separation between neighboring terminal groups.		-
3. 绝缘隔片:用于相邻联络件的电气隔离;可事后插入;不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors;they may be inserted afterwards, and not occupy any space of track		-
4. 中心联络件:用于端子中央,实现横向桥接,螺钉头带绝缘圈,可分:2-位,3-位,5-位,10-位。 Central adaptor. used at the center of terminal for transverse bridge connection, and screw head with insulated ring, which is divided into:2-digit, 3-digit, 5-digit, 10-digit,		JQ2-4/2 JQ3-4/2 JQ10-4/2
5. 跨接联络件:10 位,可分,带 10 枚螺钉;可形成跳过某些端子的跨接。 Cross connection adaptor in 10 digit, detachable, with 10 screws, for cross connection by overlapping some terminals		-
6. 标记条:有横向和竖向两种字体,10 位。 Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.		DEK5
7. 终端固定件:对端子排终端起固定作用 (JUT2 系列通用) Terminal fixed component:mark it could be used as fixed component to terminal row's termination (universal for JUT2 series)		E/2
8. 安装轨 (NS35/7.5) Installment track (NS35/7.5)		NS35/7.5
9.终端固定件 Terminal fixed component		-
10. 安装轨 (NS35/7.5) Installment track (NS35/7.5)		NS32/15