




说明	简图	型号
JUT4-T 增强型接线端子 JUT4-T 增强型接线端子是在 JUT4 通用型接线端子的压线框下部增加了一对弹簧，使端子的防震性能增强，接线更牢固。其技术参数和附件与对应的通用型接线端子完全一致。 JUT4-4 strengthened-type wiring terminal has been added one pair of spring at bottom of wire-pressing frame of JUT4 universal wiring terminal, which could strengthen shockproof performance of terminal and make wiring soliders its technical parameter and at tachment are in accordance to corresponding univer sal wiring terminal.		JUT4-2.5T 厚 / 宽  高 7/33.6/44.3 Thickness/width  Height 额定截面 Rated section:0.5-4mm² I U (A) (V) AWG:20-12 25 600 IEC 60947-7-1
1.端板 End plate		G-JUT4-2.5
2. 分组隔板: 用于端子组间的视角及电气隔离。 Segment spacer; for visual and electric separation between neigh boring terminal groups.		-
3. 中心联络件: 用于端子中央, 实现横向桥接, 可分: 2-位,3-位,5-位,10-位。 Central adaptor.used at the center of terminal for transverse bridge connection, which is dived into:2-digit, 3-digit, 5-digit, 10-digit,		-
4. 测试插座: 与测试插头形成测试连接 Test socket; to form a testing connection by using test plug.		PSB3/10/4
5. 测试插头: 形成测试连接 Test plug: to forming test connection		MPS
6. 标记牌: Mark bar		HZB5
7.终端固定件: 对端子排终端起固定件作用。 Terminal fixed component:Imposing fixed functionon terminalrow's terminaltion		E/4
8.安装轨 (NS32/15-AL) Installment track (NS32/15-AL)		NS32/15-AL