






说明	简图	型号
端子:带通用安装在 NS32 型,或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT4-10S 厚/宽 高 12/66/54 Thickness/width Height 接线容量 Wiring capacity:0.5-10mm² I U (A) (V) AWG:20-8 25 600 IEC 60947-7-1
1.端板 End plate		G-JUT4-10S
2.分组隔板: 用于端子组间的视角及电气隔离。 Insulating spacer:for visual and electric separation between neighboring terminal groups.		JAH-10S
3. 绝缘隔片: 用于相邻联络件的电气隔离; 可事后插入; 不占导轨任何空间。 Insulating spacer; for electric separation of two neighboring adaptors;they may be inserted afterwards, and not occupy any space of track		JFH-10S
4.边插式联络件: 全绝缘 2 位; 全绝缘 3 位, 全绝缘 10 位。 Side adaptor:Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit		-
5.中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 可分: 2-位,3-位,5-位,10-位。 Central adaptor. used at the center of terminal for transverse bridge connection, and screw head with insulated ring, which is divided into:2-digit, 3-digit, 5-digit, 10-digit,		-
6. 测试插头: 与测试插座形成测试连接 Test plug: to form a testing connection by using test socket.		PSB4/7/6
7. 标记条: 有横向和竖向两种字体, 10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced.		-
8. 终端固定件: 对端子排终端起固定作用 (JUT2 系列通用) Terminal fixed component:mark it could be used as fixed component to terminal row's termination (universal for JUT2 series)		PS
9. 安装轨 (NS35/7.5) Installment track (NS35/7.5)		HZB9
10.终端固定件 Terminal fixed component		E/4
11.安装轨 (NS35/7.5) Installment track (NS35/7.5)		NS32/15-AL