



说明	简图	型号
端子：带通用安装在 NS32 型，或 NS35 型导轨上。 Terminal:with general-purpose mounting feet ,can be installed on tracks NS32 or NS35		JUT1-10RD 厚/宽 高/ 高 12/62/59/64 Thickness/width Height/ Height 适用于 G 型保险丝规格 G type fuse specification 5X20 刚性导线(mm²) 柔性导线(mm²) U Rigid cable Solf cable (V) AWG:20-6 0.5-16 0.5-10 AC800 IEC 60947-7-1
带发光显示适用于电压 The product with luminous dis-play is applied to voltage of AC/DC: 15-30V 电流 current:1-2.5mA		JUT1-10RD/LED24
带发光显示适用于电压 The product with luminous dis-play is applied to voltage of AC/DC:110-250V 电流 current:0.5-1mA		JUT1-10RD/LA250
2. 边插式联络件：全绝缘 2 位；全绝缘 3 位，全绝缘 10 位。 Side adaptor:Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit		JEBS10-16
3. 中心联络件：用于端子中央，实现横向桥接，螺钉头带绝缘圈，可分：2-位,3-位,5-位,10-位。 Central adaptor. used at the center of terminal for transverse bridge connection, and screw head with insulated ring,which is dived into:2-digit, 3-digit, 5-digit, 10-digit,		JFB10-16
4. 测试插座：与测试插头形成测试连接 Test socket; to form a testing connection by using test plug.		PSB4/4/7/6
5. 测试插头：与测试插座形成测试连接 Test plug; to form a testing connection by using test socket.		PS
6. 标记条：有横向和竖向两种字体，10 位。 Mark bar: two character styles,with horizontal and vertical arrangements,ten spaced.		ZB8